

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1-18. (Canceled).

19. (Currently Amended) A supply air terminal device, comprising:

a housing having top and side walls, and open below defining a supply air chamber from which supply air is provided and side chambers in which the supply air and circulated air from a room space is mixed;

air guiding parts arranged on both sides of a central axis of said housing, a flow path leading from said side chamber to an exterior and below said housing and through which the mixed supply air and circulated air passes being defined in said side chamber and at least in part by said air guiding parts;

a heat exchanger arranged below said supply air chamber and between said air guiding parts;

nozzles arranged in connection with said supply air chamber to direct supply air from said supply air chamber into said side chambers and induce a flow of circulated air from the room space through said heat exchanger into said side chambers;

a control device arranged in each of said side chambers placed after the heat exchanger and nozzles for controlling an induction ratio between a flow of supply air through said nozzles and the flow of circulated air through said heat exchanger induced by said nozzles,

each of said control devices including a turning damper arranged in said side chamber after said heat exchanger in a direction of flow of the circulated air and to regulate opening and closing of the flow path through which the mixed supply air and circulated air passes from said side chamber to exterior of said housing such that said damper is effective to regulate a flow of mixed supply air and circulated air from said housing; and

~~an eccentric~~ a piece which engages with said turning damper to cause rotational movement of said turning damper about a joint, said turning damper being rotatably supported about said joint, and said turning damper enabling an induction ratio Q_2/Q_1 between flows E_1 L_2 and E_2 L_1 to be controlled preferably within a range of 2-6.

20. (Previously Presented) The supply air terminal device of claim 19, wherein said heat exchanger is arranged to cool or heat the circulated air.

21. (Previously Presented) The supply air terminal device of claim 19, wherein said housing includes side plates, each of said side chambers being partially defined by a respective one of said side plates.

22. (Previously Presented) The supply air terminal device of claim 19, wherein said housing includes side plates and end walls, each of said side chambers being defined by said end walls and a respective one of said side plates.

23. (Previously Presented) The supply air terminal device of claim 19, wherein said side chambers are arranged at least partially below said supply air chamber.

24. (Previously Presented) The supply air terminal device of claim 19, wherein said air guiding parts are arranged to cause the mixed supply air and circulated air to flow to a side of said housing.

25. (Previously Presented) The supply air terminal device of claim 19, wherein said housing has a longitudinal dimension, said damper of each of said control devices extending longitudinally.

26. (Previously Presented) The supply air terminal device of claim 19, wherein each of said control devices further includes a joint for supporting said damper and to enable said damper to be positioned in any one of a plurality of different positions.

27. (Cancelled)

28. (Currently Amended) The supply air terminal device of claim ~~27~~ 19, wherein said turning damper is rotatably supported about a joint, said ~~adjustment means comprising piece~~ comprises an eccentric piece engaging with said damper to cause rotational movement of said

damper about said joint.

29. (Previously Presented) The supply air terminal device of claim 19, wherein the flow path is defined between said housing and each of said air guiding parts.

30. (Previously Presented) The supply air terminal device of claim 19, wherein said heat exchanger is arranged between said dampers.

31. (Previously Presented) The supply air terminal device of claim 19, wherein said housing is closed at its top and on its sides.

32. (Previously Presented) The supply air terminal device of claim 31, wherein said housing is closed by end walls, side plates and said supply air chamber.